4105 40 hp Compact Utility Tractor





Quick and powerful at a compact price.

The affordable John Deere 4105 Compact Utility Tractor is built for hard work without the hassle, especially when it comes to loading, mowing, grading, backhoe work and many other job site and property care jobs.

It comes standard-equipped with a smooth hydrostatic transmission – no clutching or shifting. And the Twin Touch[™] pedals give you effortless speed control, ideal for inexperienced operators.

Plus – the 4105 also offers you standard 4-wheel drive, power steering, and a Category 1 hitch compatible with dozens of implements. Take a closer look – and see how this rugged workhorse is the true definition of "more bang for your buck."

Effortless power steering even during loader operation.





The H165 Loader paired with a Frontier 4-in-1 Bucket makes moving loose material fast and easy.

An optional canopy is available to make tractor work more comfortable during the elements. (LVB25334) 40.5 HP Yanmar Liquid-Cooled Diesel Engine. Efficient diesel engine that offer deep reserves of torque for handling tough loads.

Quik-Park[™] H165 Loader can be attached and detached in less than three minutes with no tools.

Roll Over Protective Structure (ROPS) certified to ASAE standards.

Optional cruise control provides effortless control while reducing operator fatigue and increasing productivity.

-116

JOHN

Adjustable seat moves both fore and aft, and also flips forward for protection from the elements.

Grab handles are located on both rear fenders to make it easier for you to get on and off the tractor. A cup holder is located on the right rear fender for convenience.

Four-wheel drive and differential lock dig in during loader work or traveling over challenging ground.

Optional iMatch[™] Quick Hitch makes lining up and attaching rear implements a snap.

FRONTIER

A left-side step allows for easy access on and off the tractor. The foot platform has a non-skid surface for sure footing.

4105 DIMENSIONS AND SPECIFICATIONS



MIN. WIDTH: 30.5 in. (775 mm) / 32.1 in. (816 mm)



Add More

Whether it's enhanced productivity, stability, visibility, or hours in the field, these attachments will help you get the most out of your John Deere Tractor.



Add more hours. LVB25546 Fwd. lighting kit (2 lights)



Add more traction. T19293 Rear wheel weights



Add more stability. LVBM19607 Front weight bracket



Add more capability. SB1148 Rear mount snow blower



Add more versatility. RB5072 Rear blade

Add more protection.

BW16040 Hood Guard

ENGINE	
Туре	Yanmar 3-cylinder diesel
HP*	40.5 (30.2 kW)
PTO HP	32.5 (24.2 kW)
Engine Displacement	91.5 cu. in. (1.5 L)
ELECTRICAL	
Battery Capacity	500 CCA
Alternator	40 amps
HYDRAULICS	
Steering	5.7 gpm (21.6 L/min)
Implement	9.2 gpm (34.7 L/min.)
Total Capacity	14.8 gpm (56.2 L/min.)
Lift Capacity (24 in. Behind Link Arms)	2,200 lb. (999 kg)
TRANSMISSION	
Standard Transmission	Hydrostatic
Final Drive	Planetary gear
Brakes	Wet disk
Steering	Power
Clutch	Wet disk
4WD	Standard
РТО	
РТО Туре	Independent
PTO Location	Rear standard
REAR HITCH	
Туре	Category 1
Control Type	Position
Weight	
With All Fluids	N/A
	4WD 2,987 lb. (1355 kg)
TIRE OPTIONS	Bar Tread/R1, Industrial/R4
ROLL OVER PROTECTIVE STRUCTURE	Fixed
H165 Loader Lift Capacity at full height, Measured at pivot	1393 lb. (633 kg)



This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specification, design and price of the products described in this literature without notice. John Deere's green and yellow color scheme, the leaping deer symbol, and JOHN DEERE are trademarks of Deere & Company. DSAE65582 (15-11) Litho in the U.S.A.

