

# HSE Series

Hot Water Electric  
Direct Drive

### Pump:

- Forged brass manifold
- Thermal relief valve
- High pressure detergent injector (Available as an option on OMM11 models)

### Motor:

- Totally enclosed fan-cooled electric motor with manual thermal overload protection
- 35-foot power cord

### Frame:

- Reinforced powder coated steel tube frame
- Flat-free tires

### Components:

- Energy-efficient top-fired heat exchanger
- No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)

### Miscellaneous:

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

### Unit Includes:

- Quick connect nozzles - 0°, 15°, 25° & 40°
- 50-foot x 3/8-inch steel wire-braided pressure hose with quick connects
- Insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance

### Limited Warranties:

- 1 year electric motor
- 3 year coil
- 7 year pump

### Certifications:

- CSA Certified - US & Canada



NEMA 5-15P, 15-amp plug    NEMA 5-20P, 20-amp plug    NEMA 6-20P, 20-amp plug

To see more online, scan here  
or go to [www.mitm.com](http://www.mitm.com)



The HSE Series of direct drive pressure washers are built to clean fast and efficiently and are ideal for cleaning grime and grease. They feature a top fired heat exchanger and a totally enclosed fan-cooled electric motor.



HSE-2003-OMG10

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	Mi-T-M NO.	PLUG TYPE	BURNER FUEL TANK CAP.	BURNER FUEL CONS.	BTU PER HOUR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
HSE-1002-OMG10	1000	2.0	1.5 HP, 120V, 1Ø, 15.0A	General	3-0071	NEMA 5-15P	4.0 gallon	1.33 gph	186,000	43x29.5x36.5in.	418 lb.	295 lb.
HSE-1002-OMM11	1000	2.0	1.5 HP, 120V, 1Ø, 15.0A	Mi-T-M	3-0383	NEMA 5-15P	4.0 gallon	1.33 gph	186,000	43x29.5x36.5in.	410 lb.	237 lb.
HSE-1502-OMG10	1500	2.0	2.0 HP, 120V, 1Ø, 19.0A	General	3-0071	NEMA 5-20P	4.0 gallon	1.21 gph	169,000	43x29.5x36.5in.	422 lb.	299 lb.
HSE-1502-OMM11	1500	2.0	2.0 HP, 120V, 1Ø, 19.0A	Mi-T-M	3-0383	NEMA 5-20P	4.0 gallon	1.21 gph	169,000	43x29.5x36.5in.	414 lb.	291 lb.
HSE-2003-OMG10	2000	2.8	4.0 HP, 230V, 1Ø, 18.0A	General	3-0168	NEMA 6-20P	4.0 gallon	1.48 gph	207,200	43x29.5x36.5in.	439 lb.	316 lb.
HSE-2003-OMM11	2000	2.8	4.0 HP, 230V, 1Ø, 18.0A	Mi-T-M	3-0384	NEMA 6-20P	4.0 gallon	1.48 gph	207,200	43x29.5x36.5in.	431 lb.	308 lb.

### Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	HX-0239	300°F steam	HSE-1002-OMM11
850-0433	50-ft. x 3/8-in. hose	All models	HX-0240	300°F steam	HSE-2003-OMG10
HX-0232	300°F steam	HSE-1002-OMG10	HX-0241	300°F steam	HSE-2003-OMM11
HX-0233	Adjustable thermostat, 86°-248°F	All models	HX-0243	Auto start/stop	2000-PSI models
HX-0235	Hour meter	All models	HX-0244	Time delay shutdown	2000-PSI models
HX-0237	Auto start/stop	1000 to 1500-PSI models	HX-0245	300°F steam	HSE-1502-OMM11
HX-0238	Time delay shutdown	1000 to 1500-PSI models	HX-0246	300°F steam	HSE-1502-OMG10